

M008-M01.SZ4130.NE6181G.EP5

GENAREL FEATURES

HP	1/3
APPLICATION	-5/+45°C
Q (Watt)	730
P (Watt)	439
Q+P (Watt)	1.169
DISCHARGE LINE	1/4"
LIQUID LINE	1/4"
SUCTION LINE	3/8"
REFRIGERANT	R-404A
CONDENSER CAPACITY (Watt) DT = 13 °C	1.670
EVAPORATOR CAPACITY (Watt)	1.082

TECHNICAL FEATURES

COMPRESSOR	Embraco NEK 6181 GK
CONDENSER	KM-130-CNT0.5 MONOBLOCK KONDANSER R404A
BODY	MONOBLOCK MODEL 1 BODY
CONDENSER FAN	Ziehl-Abegg S 300 CR46MG030W04A1 Fan Motoru 029389
DRAYER	Danfoss 023Z4552 DML 032S dryer 1/4" solder
HIGH PRESSURE CONTROL	Danfoss 061F9054 ACB-2UC56W Y.B.O. 21,0/28,0 bar
EVAPORATOR	EM-125-CNT1 MONOBLOCK EVAPORATOR R404A
EVAPORATOR FAN	Ebm S4S250-AI02-01-61
EXPANSION VALVE	Danfoss 068Z3414 TES 2 R404A (İç. D.-Kay.) MOP N
ORIFICE	Danfoss 068-2003 T2 / TE2 NO:00 Orifice
RESISTANCE	Heating/resistor rod (0,45 Kw / 395 mm)
DIGITAL CONTROL UNIT	Danfoss 080G3265 KIT ERC 213 230V
ELECTRICAL PANEL	Electric Panel Monofaze

