

## M036-M02.SZ4130.NT6224G.EP5

### GENAREL FEATURES

HP	1,00
APPLICATION	-5/+45°C
Q (Watt)	1.933
P (Watt)	1.145
Q+P (Watt)	3.078
DISCHARGE LINE	1/4"
LIQUID LINE	1/4"
SUCTION LINE	3/8"
REFRIGERANT	R-404A
CONDENSER CAPACITY (Watt) DT = 13 °C	4.060
EVAPORATOR CAPACITY (Watt)	2.418

### TECHNICAL FEATURES

COMPRESSOR	Embraco NT 6224 GK
CONDENSER	KM-130-CNT2 MONOBLOCK CONDENSER R404A
BODY	MONOBLOCK MODEL 2 BODY
CONDENSER FAN	Ziehl-Abegg S 300 CR46MG030W04A1 Fan Motor 029389
DRAYER	Danfoss 023Z4552 DML 032S dryer 1/4" solder
HIGH PRESSURE CONTROL	Danfoss 061F9054 ACB-2UC56W Y.B.O. 21,0/28,0 bar
EVAPORATOR	EM-130-CNT2 MONOBLOCK EVAPARAToR R404A
EVAPORATOR FAN	Ziehl-Abegg S 300 CR46MG030W04A1 Fan Motor 029389
EXPANSION VALVE	Danfoss 068Z3415 TES 2 R404A (Diş D.-Kay.) MOP N
ORIFICE	Danfoss 068-2015 T2 / TE2 NO:02 Orifice
RESISTANCE	heating/resistor rod (0,50 Kw / 480 mm)
DIGITAL CONTROL UNIT	Danfoss 080G3265 KIT ERC 213 230V
ELECTRICAL PANEL	Electric Panel Monofaze

